

# DANTHERM

COOLING

## PrecisionAir®

*Performance Electrical Cabinet HVAC and Heat Pump Cooling Systems*



**DANTHERM**  
COOLING

**DANTHERMCOOLING.COM**

TECHSUPPORT@DANTHERMCOOLING.COM | 864-595-9800

671 SPRINGFIELD ROAD | SPARTANBURG, SOUTH CAROLINA 29303



## ***About Dantherm Cooling***

### *Performance Cooling*

Over the past 28 years, Dantherm cooling has established itself as a leader in innovative cooling systems, supplying more than 300,000 climate control units to mission critical applications. By applying our passion for performance and quality throughout our company, we have become known for providing outstanding products and an exceptional customer experience.

Our innovative, highly engineered product lines feature industry leading technology to deliver outstanding performance, operate efficiently and perform reliably in extreme climate conditions. Backed by our experienced design team, quality manufacturing processes and extensive testing and certification practices, Dantherm Cooling can provide customers with engineered solutions to their most challenging applications.

Our passion and success in building an industry leading business compels us to invest in those around us. From our employee centric culture, to our ongoing community outreach, we are committed to use our business a catalyst for positivity in the lives of those around us.



## **PrecisionAir®**

PrecisionAir cabinet cooling systems are designed with performance in mind. Our systems draw warm air from the top of a cabinet or enclosure, then transfer the heat out, and return cool air to the bottom of the enclosure while ensuring that dust, contaminants, and moisture stay out. Closed-loop technology helps maintain a clean internal environment with minimum maintenance, for optimal performance and maximum service life of the electronics inside the cabinet or enclosure. As a result, PrecisionAir units deliver superior cooling, far outperforming commercial air conditioning units.

Dantherm PrecisionAir cabinet cooling systems are easy to install and engineered for use in a wide range of cooling capacities. Having been widely installed on mission-critical equipment and in digital infrastructure applications, customers have grown to trust their proven reliability and exceptional performance.

A wide range of options, capacities and features along with refined manufacturing processes make the PrecisionAir series adaptable for a wide range of critical infrastructure applications where performance and reliability are of the utmost concern.

# PrecisionAir®

## Energy Efficient Cooling For Any Equipment Enclosure

At Dantherm Cooling, innovation is a critical part of who we are. In fact, pursuing innovation is one of our core values. Our PrecisionAir cabinet cooling systems utilize our extensive engineering and manufacturing expertise to deliver energy-efficient cooling for any equipment enclosure.

All of our products are manufactured to exacting tolerances and thoroughly tested before they leave our factory. With over 300,000 units operating in mission critical applications, customers can be assured of long life and industry leading performance.

- Compact, self-contained design for easy installation in indoor and outdoor applications
- Closed-loop cooling prevents ingress of contaminants
- High-performance BCI fans have high-static pressure capability for improved air flow while reducing noise and energy usage
- Bottom outside air loop intake allows for reduced noise and better protection from contaminants
- Easy access to critical components for better serviceability
- Integrated ACG7 controller available with ethernet featuring SNMP Ver2 or Modbus with web-based GUI

## Engineered Performance

### Designed to Meet Demanding Customer Requirements

#### **Energy Efficient**


Engineered performance with high-static BCI fans uses 40-60% less energy

#### **Optimized Cooling**

Powerful cooling designed to perform in high ambient temperatures

#### **Quiet Performance**

Designed to reduce noise, making PrecisionAir ideal for sound-sensitive applications at 60-65 dB



#### **Reliable**

Closed loop design, all aluminum microchannel coil and weatherproof enclosure for the most challenging environments

#### **Connected**

Monitor and manage thermal environment from your desk with integrated ACG7 Smart Controller

#### **Low Maintenance**

Easy to install with minimal maintenance requirements

## PrecisionAir®

*Verified Performance, Quality Assured*

Dantherm Cooling's commitment to high-quality innovation, manufacturing and customer support is demonstrated by the standards we keep.

Our products are routinely used in critical infrastructure applications where our customers require the highest performance, quality and reliability standards. Third party certification and verification gives customers a sense of security knowing that our products have been independently tested to perform to the caliber we claim.



Dantherm Cooling's ISO 9001:2105 certification demonstrates that our business and manufacturing processes meet all international standards for the consistent delivery of high-quality products and services. Regular audits and process reviews ensure consistent manufacturing performance.



Through our partnership with Underwriter's Laboratory (UL), UL has certified that all Dantherm Cooling materials and products, as well as specific testing procedures and documentation, have been thoroughly inspected for safety and quality, and meet or exceed established standard requirements.

# PrecisionAir®

*Engineered for a Wide Variety of Applications*

## **Telecom**

PrecisionAir units from Dantherm are ideally suited for telecom buildings which require energy efficient cooling for the valuable electronic equipment held inside. Dantherm Cooling units offer improved design techniques and high quality components to optimize cooling performance and energy efficiency while requiring little maintenance.



## **Battery Energy Storage (BESS)**

Battery energy storage applications require reliable performance cooling to improve storage conditions and optimize battery life. Dantherm's PrecisionAir units offer reliable performance, high quality BCI fans and Dantherm's integrated ACG7 controller to offer consistent ideal temperatures, improving the performance of your system.



## **Electric Grid T&D Control Houses**

Demanding electric grid relay switching T&D control houses require sufficient thermal control to keep equipment running smoothly. PrecisionAir units are designed to operate efficiently in extreme conditions, weather and the wide-range of outdoor environments energy professionals must operate in.



## **Mobile Modular**

Mobile modular buildings such as job site construction buildings or modular school buildings require adequate climate control solutions to create environments conducive to learning and work. Dantherm's cooling solutions offer energy efficient, powerful cooling and are designed to operate quietly making them an ideal choice for these environments.




# DANTHERM

COOLING

## PrecisionAir®

*Technical Specifications*



# PrecisionAir®

## Configure Your Own PrecisionAir System

PrecisionAir cabinet cooling systems offer a wide variety of options with versatility for a number of applications and conditions in mind. A number of product options are available allowing each unit to be tailored specifically for the application in which it will be applied.

All of our products are manufactured to exacting tolerances and thoroughly tested before they leave

our factory. With over 300,000 units installed in the field in a variety of industries Dantherm products are proven performers.

- Multiple heater options available
- AC and DC powered units available
- Environmentally friendly R134A refrigerant
- Wide range of color and finish options

### PA-10-230-F-ET-SS-03

**CAPACITY**  
4 - 4000 BTU  
6 - 6000 BTU  
10 - 10000 BTU  
12 - 12000 BTU  
14 - 14000 BTU  
24 - 24000 BTU  
28 - 28000 BTU

**VOLTAGE**  
115 - 115 VAC  
230 - 230 VAC  
48 - 48 VDC


**OPTIONAL FILTER**  
H - STANDARD MERV8  
M - MERV13  
F - FRESH AIR

**OPTIONAL METAL PACKAGE**  
SS - STAINLESS STEEL\*  
\*LEAVE BLANK - STANDARD GALVANIZED STEEL

**OPTIONAL ETHERNET CONTROLLER**  
ET - ETHERNET CONTROLLER

**COLOR**  
03 - P03 GREY  
04 - P04 BEIGE  
20 - P20 WHITE  
00 - CUSTOM


### Color Options




03 - P03 Grey



04 - P04 Beige



20 - P20 White









00 - Custom



# PrecisionAir® 2000

## Capacity Curve & Dimensional Drawings



**NOTES:**

- 1) UNITS = MM [IN]
- 2) STEP FILES AVAILABLE ON REQUEST




# PrecisionAir® 2000

## Technical Data

	UNITS		
MODEL NUMBER		PA-2-115	PA-2-230
MOUNTING METHOD		Outdoor	
UNIT DIMENSIONS [HxWxD]	Inches	20.25x10.4x10.6	
WEIGHT	Lbs	55	
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	2480 [726]	
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	2160 [629]	
INTERNAL AIRFLOW	CFM [m³/h]	100 [170]	
EXTERNAL AIRFLOW	CFM [m³/h]	100 [170]	
REFRIGERANT	Type	R134a	
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]	
NOISE 1.5M DISTANCE	dB	64	
HEATER	Watts	500	
INPUT VOLTAGE /FREQUENCY	Volts/Hz	115 VAC / 230 VAC 50/60Hz	
POWER CONSUMPTION	Amps	8.0	4.0
APPROVALS		SA10718 (UL)	
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available	

# PrecisionAir® 4000

## Dimensional Drawings



- NOTES:**
- 1) UNITS = MM [IN]
  - 2) STEP FILES AVAILABLE UPON REQUEST




# PrecisionAir® 4000

## Technical Data

	UNITS				
MODEL NUMBER		PA-4-115	PA-4-230	PA-4-460/3	PA-4-48
MOUNTING METHOD		Outdoor			
UNIT DIMENSIONS [HxWxD]	Inches	29.0x17.3x11.3			
WEIGHT	Lbs	75			90
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	4270 [1250]			4200 [1230]
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	4235 [1240]			4000 [1170]
INTERNAL AIRFLOW	CFM [m³/h]	247 [420]			
EXTERNAL AIRFLOW	CFM [m³/h]	247 [420]			
REFRIGERANT	Type	R134a			
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]			
NOISE 1.5M DISTANCE	dB	<62			<65
HEATER	Watts	1000			500
INPUT VOLTAGE /FREQUENCY	Volts/Hz	115 VAC [60 Hz]	230 VAC [50/60 Hz]	460 VAC [50/60 Hz]	48 VDC
POWER CONSUMPTION	Amps	8.9	5.8	2.3	12
APPROVALS		4010388 (ETL)		-	SA10718 (UL)
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available			

# PrecisionAir® 6000

## Dimensional Drawings



- NOTES:**
- 1) UNITS = MM [IN]
  - 2) STEP FILES AVAILABLE UPON REQUEST




# PrecisionAir® 6000

## Technical Data

	UNITS				
MODEL NUMBER		PA-6-115	PA-6-230	PA-6-460/3	PA-6-48
MOUNTING METHOD		Outdoor			
UNIT DIMENSIONS [HxWxD]	Inches	29.0x17.3x11.3			
WEIGHT	Lbs	80			95
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	6000 [1750]			
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	6170 [1806]			
INTERNAL AIRFLOW	CFM [m³/h]	247 [420]			
EXTERNAL AIRFLOW	CFM [m³/h]	247 [420]			
REFRIGERANT	Type	R134a			
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]			
NOISE 1.5M DISTANCE	dB	<65			
HEATER	Watts	1000			500
INPUT VOLTAGE /FREQUENCY	Volts/Hz	115 VAC [60 Hz]	230 VAC [50/60 Hz]	460 VAC [50/60 Hz]	48 VDC
POWER CONSUMPTION	Amps	10.0	7	3.0	16
APPROVALS		4010388 (ETL)		-	SA10718 (UL)
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available			

# PrecisionAir® 10000

## Dimensional Drawings



- NOTES:**
- 1) UNITS = MM [IN]
  - 2) STEP FILES AVAILABLE UPON REQUEST

# PrecisionAir® 10000




## Technical Data

	UNITS		
MODEL NUMBER		PA-10-230	PA-10-48
MOUNTING METHOD		Outdoor	
UNIT DIMENSIONS [HxWxD]	Inches	47.3x19.3x12.2	
WEIGHT	Lbs	115	
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	10700 [3133]	
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	10170 [2977]	
INTERNAL AIRFLOW	CFM [m³/h]	210 to 450[765]	
EXTERNAL AIRFLOW	CFM [m³/h]	400 to 710 [1205]	
REFRIGERANT	Type	R134a	
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]	
NOISE 1.5M DISTANCE	dB	60 to 65	
HEATER	Watts	2000	500
INPUT VOLTAGE /FREQUENCY	Volts/Hz	208/230 VAC [50/60 Hz]	48 VDC, +20%/-15%
POWER CONSUMPTION	Amps	11.0	29.0
APPROVALS		SA10718 (UL)	
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available	



# PrecisionAir® 12000

## Dimensional Drawings



- NOTES:**
- 1) UNITS = MM [IN]
  - 2) STEP FILES AVAILABLE UPON REQUEST




# PrecisionAir® 12000

## Technical Data

	UNITS		
MODEL NUMBER		PA-12-230	PA-12-48
MOUNTING METHOD		Outdoor	
UNIT DIMENSIONS [HxWxD]	Inches	47.3x19.3x12.2	
WEIGHT	Lbs	115	
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	11300 [3000]	
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	10300 [3000]	
INTERNAL AIRFLOW	CFM [m³/h]	210 to 450[760]	
EXTERNAL AIRFLOW	CFM [m³/h]	400 to 710 [1205]	
REFRIGERANT	Type	R134a	
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]	
NOISE 1.5M DISTANCE	dB	60 to 65	
HEATER	Watts	2000	500
INPUT VOLTAGE /FREQUENCY	Volts/Hz	208/230 VAC [50/60 Hz]	48 VDC, +20%/-15%
POWER CONSUMPTION	Amps	11.0	29.0
APPROVALS		SA10718 (UL)	
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available	

# PrecisionAir® 14000

## Dimensional Drawings



- NOTES:**  
 1) UNITS = MM [IN]  
 2) STEP FILES AVAILABLE UPON REQUEST






# PrecisionAir® 14000

## Technical Data

	UNITS	
MODEL NUMBER		PA-14-48
MOUNTING METHOD		Outdoor
UNIT DIMENSIONS [HxWxD]	Inches	47.3x19.3x12.2
WEIGHT	Lbs	115
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	14000 [4100]
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	12100 [3545]
INTERNAL AIRFLOW	CFM [m³/h]	210 to 450[765]
EXTERNAL AIRFLOW	CFM [m³/h]	400 to 710 [1205]
REFRIGERANT	Type	R134a
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]
NOISE 1.5M DISTANCE	dB	60 to 65
HEATER	Watts	500
INPUT VOLTAGE /FREQUENCY	Volts/Hz	48 VDC, +20%/-15%
POWER CONSUMPTION	Amps	27.0
APPROVALS		SA10718 (UL)
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available

# PrecisionAir® 20000

## Dimensional Drawings



- NOTES:**  
 1) UNITS = MM [IN]  
 2) STEP FILE AVAILABLE UPON REQUEST







# PrecisionAir® 20000

## Technical Data

	UNITS	
MODEL NUMBER		PA-20-230
MOUNTING METHOD		Outdoor
UNIT DIMENSIONS [HxWxD]	Inches	61x19x20
WEIGHT	Lbs	200
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	20400 [6030]
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	19800 [5800]
INTERNAL AIRFLOW	CFM [m³/h]	1250[2120]
EXTERNAL AIRFLOW	CFM [m³/h]	1250 [2120]
REFRIGERANT	Type	R134a
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]
NOISE 1.5M DISTANCE	dB	60 - 65
HEATER	Watts	2000
INPUT VOLTAGE /FREQUENCY	Volts/Hz	208/230 VAC
POWER CONSUMPTION	Amps	15.0
APPROVALS		SA10718 (UL)
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available

# PrecisionAir® 24000

## Dimensional Drawings



- NOTES:**  
 1) UNITS = MM [IN]  
 2) STEP FILE AVAILABLE UPON REQUEST

# PrecisionAir® 24000







## Technical Data

	UNITS		
MODEL NUMBER		PA-24-230	PA-24-48
MOUNTING METHOD		Outdoor	
UNIT DIMENSIONS [HxWxD]	Inches	59x24.3x20.2	
WEIGHT	Lbs	230	
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	24000	
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	22000	
INTERNAL AIRFLOW	CFM [m³/h]	800[1360]	
EXTERNAL AIRFLOW	CFM [m³/h]	1400 [2380]	
REFRIGERANT	Type	R134a	
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]	
NOISE 1.5M DISTANCE	dB	65	
HEATER	Watts	2000	1000
INPUT VOLTAGE /FREQUENCY	Volts/Hz	208/230 VAC [50/60Hz]	48 VDC, +20%/-15%
POWER CONSUMPTION	Amps	20.0	60.0
APPROVALS		SA10718 (UL)	
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available	



# PrecisionAir® 28000

## Dimensional Drawings



NOTES:  
1) UNITS = MM [IN]

NOTE SPECIFIED:

# PrecisionAir® 28000

## Technical Data

	UNITS	
MODEL NUMBER		PA-28-48
MOUNTING METHOD		Outdoor
UNIT DIMENSIONS [HxWxD]	Inches	59x24.3x20.2
WEIGHT	Lbs	230
COOLING CAPACITY 131°F INTERNAL / 131°F AMBIENT	BTU/h [W]	28000
COOLING CAPACITY 95°F INTERNAL / 95°F AMBIENT	BTU/h [W]	26000
INTERNAL AIRFLOW	CFM [m <sup>3</sup> /h]	800[1360]
EXTERNAL AIRFLOW	CFM [m <sup>3</sup> /h]	1400 [2380]
REFRIGERANT	Type	R134a
OPERATIONAL TEMPERATURE RANGE	°F [°C]	-40 to 131 [-40 to 55]
NOISE 1.5M DISTANCE	dB	65
HEATER	Watts	1000
INPUT VOLTAGE /FREQUENCY	Volts/Hz	48 VDC, +20%/-15%
POWER CONSUMPTION	Amps	60.0
APPROVALS		SA10718 (UL)
CONSTRUCTION		Galvanized Steel, Stainless Optional Textured Powder Coat, Color Options Available

**DANTHERM**  
COOLING

**DANTHERMCOOLING.COM**

**TECHSUPPORT@DANTHERMCOOLING.COM 864-595-9800**

**671 SPRINGFIELD ROAD SPARTANBURG, SOUTH CAROLINA 29303**